

Model No. WPS1516DSLKC



Camera Head		Monitor		Control Box	
Camera Size:	ø50mmXL84mm	Size:	15 inch TFT color	Work current/supply:	150MA / DC12V
Spring:	ø22.3mmX160mm	Total Pixels:	800X600	Storage medium:	8G SD card(max 32G) SD card reader
Transmitter:	512Hz	Power supply:	DC 12V	Battery level display	
Sensor size:	1/3 inch Sony CCD	Power consumption:	24W	Picture snap & movie record	
View angle:	90°	OSD language:	English	DVR Total Pixels:	720X576 (D1)
Work current/supply:	250MA / DC12V	Model:	4:3	Movie format:	AVI
Camera light:	30PCS white LEDs	Accumulator		Microphone Audio record	
Pixels:	960TVLine	Total Power:	30W	Stereo earphone output	
Glass material:	Sapphire glass	Charge time:	12 hours	Keyboard	
Shell material:	Aluminum alloy	Work time:	≥260minutes	Size:	323(L)X130(W)X11(H)m
Self-levelling function		Suitcase		Language:	English
Cable Wheel		Size:	L460XW370XH180mm	Interface:	USB
Cable size:	770LX371WX810Hmm	Material:	Engineering plastics	Text Edit Line:	PAL 27letter 14line NTSC 27letter 12line
Wire material:	Fiberglass rod	Charger		Max Edit Page:	4pages
Wire length:	60m/120m(standard)	Input:	AC100-240V~50/60Hz	Skids	
Wire diameter:	ø9mm	Output:	DC 12V/1000MA	Skid -1 / -2 / -3	ø110 / ø150 / ø220mm
Wheel material:	Stainless steel	DC plug diameter:	2.1mm		
Meter counter & handle-brake					
Fiberglass color:	Yellow				



Camera



Control Box



Cable Wheel



Monitor



Accumulator



Charger



Skids



Suitcase



Keyboard